

## Short throw Education focused Super stable

The InFocus IN226ST short throw projector greatly fits education circumstance with its short throw feature, long lamp life, super cooling system, and robust dust prevent filter.

This value-packed projector is easy to buy and built to perform with high brightness, high contrast ratio and BrilliantColor™ technology.



IN226ST

XGA (1024X768)

3200 lm

### Why choose the IN226ST?

- Short throw
- Revolutionary thermal design
- Remove dusty-proof filter
- Easy to use connectivity
- High brightness
- High contrast ratio
- 3D technology supports up to 120 Hz frame rate
- Compact design and weights only 2.35kg
- Accurate and vivid color reproduction with BrilliantColor technology



#### Connections

VGA-in\*2, Composite video, S-video, Audio-in\*2, mini USB, HDMI, VGA-out, Audio-out, RS232

### High efficient cooling system

New designed structure with vertical positioned main board creates a straight and wide air passage. Assisted by strong and robust cooling fans, times the volume of input air comparing to traditional design generates very high efficient cooling effect.

### Abundant connections

No matter in what scenario and purpose you need to use a IN220 series projector, it can always provide you a correspondent connection to satisfy your operation.

### Extra intensive dust proof (Optional)

Besides sealed optic engine to provide best dusty prevention, a pair of removable dust proof filters is installed at the air intake to provide extra protection from dust, which is easy to take off and clean.

### High cost efficiency

Not only affordable prices deliver benefits to our customers, but also helped by the new designed cooling and dusty proof systems, IN220 series products have longer life time and default free performance, which lower down keeping and operating cost.

# Specification

## IN226ST

Native Resolution	XGA
Brightness	3200 lumens
Contrast Ratio	17000:1
Display Technology	DLP 0.55" DDP4421
Color Wheel	6 Segment
Aspect Ratio	4 : 3
Projection Lens	2.8
Uniformity	80%
Throw Ratio	0.626
Throw Distance	0.75 m to 3.82 m
Zoom Ratio	NA
Keystone Correction	±40° Vertical
Noise	32dB (normal) / 29dB (eco)
Input	VGA-in*2, Composite video, S-video, Audio-in*2, mini USB, HDMI
Output	VGA-out, Audio-out
Control	RS232
Video Compatibility	PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz)
Lamp	190W
Lamp Life	5000 Hours (Normal) / 6000 Hours (Eco)
H-Synch Range	15.3 - 91.1KHz
V-Synch Range	24~85Hz
Standby	<0.5W
Power consumption	225W bright mode/191W eco mode
Power supply	100~240V AC @ 50~60 HZ
Operating Temp.	5°C~40°C
Storage Temp.	-10°C~60°C
Demission	314.3x223.6x88.2 mm (w/o feet)
Weight	2.35 kg
Standard Accessories	User Manual (CD), Safety/Reg card, VGA cable, Power cord, Remote control

## Warranty

Providing the highest quality products and support is very important to us. The IN226ST comes standard with a 2-year limited factory warranty and 1-year or 1000 hours lamp replacement warranty

**InFocus**  
Bright Ideas Made Brilliant

©2012 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Bright Ideas Made Brilliant are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies.

[www.infocus.com.cn](http://www.infocus.com.cn)