

## WiPG-1000

The WiPG or WePresent-1000 is a spectacular presentation tool that allows a group of **up to 64 users**, to take turns in **wirelessly** presenting from their **Win/Mac** computer, **Smartphone** or **Tablet**.

The WePresent can be connected to any TV, display or projector with **HDMI** or **VGA** connection, and can project up to **full HD resolution**!

It also supports **Touchscreens** and **Interactive White Boards**! Allowing the presentor to have full control over the projecting computer on the touchscreen, **wirelessly**!



## **Special features:**

- VGA or HDMI output, up to full HD Connect the WePresent-1000 to any HDMI / VGA display or projector and set output resolution up to Full HD!
- Conference Control

Manage up to 64 connected users as administrator and control who is projecting and where.

4-to-1 Projection

Use the WePresent software interface (or Conference Control) to choose in which screen-quadrant a projection is started.

Wireless Access Point

When connected to wired or wireless network the WePresent functions as a wireless access point, allowing internet access.

SidePad

Use your tablet or smartphone to wirelessly control the projecting PC/Mac.

WiFi-Doc

WiFi-Doc will project any Powerpoint, Excel, Word, PDF files or photos from your tablet or smartphone to the WiPG-1000.

Sender for Galaxy

With the Sender for Galaxy app it is possbile to mirror the screen from your Samsung Galaxy device to the WiPG.

BrowserSlides

Allow audience to view the speaker's current slides in their webbrowser and save them for taking notes.

- Touchscreen and Interactive White Board supported Speaker and audience can interact on touchscreen or IWB wirelessly!
- Fast Plug-and-Show USB token Allow a guest to start the WePresent software directly from a USB stick, without installing any software on their computer.





## **Basic features**

Windows/Mac support	St
WiFi-Doc and MirrorOp Presenter for iOS/Android	
Plug&Show: launching the projection application from a USB thumb drive	Se M Su
4-to-1 Quadrant Screen Projection	O
SNMP Manager: manage/configure multiple WiPGs thru SNMP consoles	Su
Conference Control: Mediator control function thru the device web page	OI
Support up to 64 logged users	In
Security design: Session Login Code, WEP/WPA key, and GateKeeper	
HDMI and VGA dual video interfaces	
WiFi AP-Client mode support	
WiFi 802.1b/g/n	Ce

## Specification

Standards	IEEE 802.11b/g/n 2.4GHz
	IEEE 802.3 (10BASE-T) / IEEE 802.3u (100BASE-TX)
Security	IEEE Standard 64/128 bit WEP / WPA / WPA2-PSK
Management	Web-based configuration
Supported	VGA:SVGA(800x600)/XGA(1024x768)
Output Resolution	/WXGA(1280x768)/WXGA(1280x800)/WXGA(1360x768)
	/WXGA+(1440x900)/UXGA(1600x1200)
	HDMI:720p(1280x720)/1080p(1920x1080)
Supported	Windows XP / Vista / 7, Mac OS X 10.5 and above,
Operation System	Android 2.2 and above, iOS 3.2 and above.
Power	External power adaptor DC 5V 2.6A
Interfaces	15Pin VGA
	HDMI
	RJ-45
	USB 2.0 x 3
	Power Button
	Reset Button
	Stereo Phone Jack
Certificate	FCC/CE
	HDMI RJ-45 USB 2.0 x 3 Power Button Reset Button Stereo Phone Jack